



# MotorVac® Universal ATF Protectant

*The Ultimate Universal ATF Protectant and Converter*

**MotorVac® Universal ATF Protectant performs four very specific functions that will benefit both your shop and your customers.**

- ✓ Eliminate stocking a wide variety of ATF's, replacing them with as few as two ATF's.
- ✓ Enhances ATF's by reducing friction and enhancing heat transfer which dramatically reduces transmission wear.
- ✓ Chemically engineered formulation eliminates shudder in converters and clutch packs to ensure smooth shifting and maximize transmission life.
- ✓ Conditions and restores seals and O-rings helping to eliminate leaks.

## Why use a Universal ATF Supplement?

Today's wide variety of transmissions require a range of fluids with different characteristics. A full service facility traditionally needed to stock several different fluids to meet these requirements. Often, they are OEM specific and very expensive. This means more money tied up in inventory and valuable storage space is wasted in the Parts Department.

### Use as an add-on Service

MotorVac® ATF Protectant can be added to almost all automatic transmissions as an added benefit. By reducing excessive heat and friction, you can prolong transmission life while ensuring smoother shifting. Your customer satisfaction levels will increase with every vehicle serviced.

Not for use in CVT applications or vehicles that require Type "F" ATF  
\*See reverse side for application chart



**MotorVac® Universal  
ATF Supplement**

Part No. 400-1030as



# MotorVac® Universal ATF Protectant can be added to the following base products to replace the corresponding Automatic Transmission Fluids

## Eliminate the Confusion

MotorVac® Universal ATF Protectant eliminates the need of stocking multiple OEM fluids. It enhances Synthetic Dexron® III, Dexron® VI or Mercon® ATF to perform like Mercon® V ATF. As well, it will enhance Dexron® or Mercon® ATF to perform like a highly friction modified ATF such as Toyota Type T, T II, T IV, Mopar ATF +3 (7176), ATF +4 (9602) or Honda Genuine Z-1 ATF.



**MotorVac® Universal ATF Supplement**  
Part No. 400-1030as

## IMPORTANT

If the vehicle is subject to severe duty (as defined in their owners manual), or operates where the temperature falls below 0° (-18° C), the use of Synthetic or Semi- Synthetic DEXRON® III, VI / MERCON® V ATF is strongly recommended. All Synthetics mentioned above are required. Only use quality ATF base oils.

OEM AUTOMATIC TRANSMISSION FLUIDS	BASE PRODUCTS		
	DEXRON® III MERCON® MERCON® V	SYNTHETIC DEXRON® III SYNTHETIC MERCON®	DEXRON® VI
Allison TranSynd (TES-295)	✓	✓	
Audi G 055 025		✓	✓
Audi G 055 182A2 /#G 055 005			✓
Esso Type LT 71141		✓	✓
Fuchs ATF 3353			✓
Honda Genuine Z-1	✓	✓	✓
Hyundai SP-III	✓	✓	✓
Idemitsu ATF HP		✓	✓
Idemitsu ATF K17			✓
Isuzu Genuine Fluid		✓	✓
Jaguar Fluid 8342			✓
KIA Red-1 #UM040CH020			✓
KIA SP-III	✓	✓	✓
Mazda V	✓	✓	✓
MB 0019892 10310		✓	✓
Mercon V	✓	✓	✓
MERCON LV			✓
MERCON SP			✓
Mitsubishi Diamond SPIII	✓	✓	✓
Mopar ATF+3 (7176)	✓	✓	✓
Mopar ATF+4 (9602)	✓	✓	✓
Nissan Matic D	✓	✓	✓
Nissan Matic J		✓	✓
Nissan Matic K			✓
SAAB P/N 93165147			✓
Saturn Transaxle Fluid 21005966		✓	✓
Shell 3403		✓	✓
Shell 3403-M115		✓	✓
Shell LA2634 or BMW 83229407765		✓	✓
Shell 3603			✓
Shell M-1375.4			✓
Shell M-1375.4 PN 83220142516 (BMW)			✓
Sterling ATF	✓	✓	✓
Subaru PN K0140Y0700		✓	✓
Texaco ETL-7045 E		✓	✓
Texaco ETL-8072 B		✓	✓
Texaco N402		✓	✓
T-IV (FORD XT-8-QAW)	✓	✓	✓
T-IV (SAAB 3309)	✓	✓	✓
T-IV (SATURN 22689186)	✓	✓	✓
T-IV (VOLVO 1161540-8)	✓	✓	✓
T-IV Suzuki 3317 or Mobil 3309		✓	✓
Toyota Type T-IV	✓	✓	✓
Toyota WS			✓
Type T-IV (AC DELCO GM 99000925)	✓	✓	✓
Type T-IV (Mini 83 22 0 402 413)	✓	✓	✓
Volkswagen G 052 182 A2			✓
Volkswagen G 052 990 A2/G 052 025 (-A2)		✓	✓